

Octanial Antifreeze Coolant 50% Concentrated

Description and Application

Octanial 50 % Coolant is a specially formulated ready-to-use engine coolant, for both petrol and diesel engines, It is mixture of mono-ethylene glycol and selected chemical agents to provide outstanding all-round protection.

Filling Instruction:

Coolant should not be further diluted while using in the system or when topping up prior to filling with the Coolant cooling system should be properly cleaned and cleared of all blockages and suspended rust and dirt in the system should be flushed with clean water. In a clean cooling system, Coolant will deliver optimum performance and protection for up to one year upon which the system should be drained and refilled with Coolant.

Main Benefits:

- Effective engine cooling without boiling.
- A clean cooling system with protection from sludge and scale deposits.
- Protection against corrosion of the alloys used in the cooling system of modern vehicles.
- Protection against frost.
- Prevention against electrolysis.
- Protection against cavitations corrosion.
- Efficient lubrication of water pumps.
- Compatibility with rubbers.

Typical Characteristics:

SR. NO	TEST PARAMETERS	TEST METHOD	TYPICAL
1)	Color	Obs	Pink
1)	Density @ 15°C gm/cm ³	ASTM D1298	1.08
2)	pH	ASTM D 1121	9.0
3)	Reflux boiling point °C	ASTM D 1120	106
4)	Freezing point °C	ASTM D 1117	-34
5)	Concentration % wt		50.00

*C&B = Clear and Bright

The above figures are typical of those obtained with normal production tolerance and do not constitute specifications