

Octanial Diesel Engine Oil SAE 10W40 API CI-4

Properties

Octanial Diesel Engine Oil SAE 10W-40 API CI-4 is a mineral oil based, high-performance Diesel Heavy-duty road transport of SAE 10W-40 viscosity grade. Mineral oils derived from the most modern refinery techniques, together with innovative Low-SAPS additives matched to them, ensure that the demands of today's practice are met. Its outstanding qualities include its excellent lubrication security at high temperatures and the exceptional wear protection under all operating conditions.

Features and Benefits

- Reduce deposits
- Anti-wear
- Long oil drain

Application

Diesel Heavy-duty road transport

Performance / Specifications

SAE Grade 10W-40

API CI-4

Typical Data	Unit	Test Method	Results
SAE Grade		SAE J300	10W-40
Density at 15 ^o C	g/ml	ASTM D4052	0.850
Apparent Viscosity at -25 ^o C	mPa s	ASTM D5293	6600
Kinematic Viscosity at 40 ^o C	mm ² /s	ASTM D445	96.6
Kinematic Viscosity at 100 ^o C	mm ² /s	ASTM D445	15.2
Viscosity Index	-	ASTM D2270	166
Flash Point	°C	ASTM D92	230
Pour Point	°C	ASTM D97	- 33
Total Base Number	mg KOH/g	ASTM D2896	10

Note: the information contained herein is subject to change without notification. Typical Properties may vary slightly.

Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment