

Octanial Gear Oil

(Gear Oil API GL-4)

Product Description

Octanial Gear Oil is designed for use in a hypoid, bevel and spiral gear units, axles and final drives operating under severe conditions and over a wide spectrum of operating conditions.

Through their mono-grade viscosity characteristics they meet the requirements of several automotive manufacturers for passenger cars and commercial trucks or buses

Features and Benefits

- Very good wear protection, even under severe load conditions.
- High safety margin against foaming and corrosion
- Superior viscosity / temperature and cold flow properties
- Compatible with all seal and metal types.

Typical Properties

Sr. No	Test Parameters	Test Method	Typical	
	SAE Grade		140	90
1)	Appearance	Visual	C&B*	C&B*
2)	Density @ 15°C gm/cm ³	ASTM D1298	0.90	0.92
3)	Viscosity Index	ASTM D2270	95	97
4)	Viscosity @ 100°C (cSt)	ASTM D 445	30.5	17.5
5)	Pour Point °C	ASTM D 97	-15	-18
6)	Flash Point (COC)°C	ASTM D 92	236	230

*Note: the information contained herein is subject to change without notification. Typical Properties may vary slightly.

Health and Safety Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment